

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/015851 A3

(51) International Patent Classification⁷: **H02P 5/34, 7/42**

[US/US]; 1641 Berkshire Hill Drive, Duluth, GA 30097-4310 (US).

(21) International Application Number:

PCT/US2003/019887

(74) Agents: **BERNSTEIN, Howard, L.** et al.; Sughrue Mion, Pllc, 2100 Pennsylvania Ave., N.W., Suite 800, Washington, DC 20037-3213 (US).

(22) International Filing Date: 31 July 2003 (31.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/399,355 31 July 2002 (31.07.2002) US
60/453,817 12 March 2003 (12.03.2003) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **SMC ELECTRICAL PRODUCTS, INC.** [US/US]; P.O. Box 880, Barboursville, WV 25504 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **NOJIMA, Geraldo**

[Continued on next page]

(54) Title: **LOW VOLTAGE, TWO-LEVEL, SIX-PULSE INDUCTION MOTOR CONTROLLER DRIVING A MEDIUM-TO-HIGH VOLTAGE, THREE-OR-MORE-LEVEL AC DRIVE INVERTER BRIDGE**



(57) Abstract: A method and circuit enabling off-the-shelf controllers designed for use with a two-level AC drive inverter bridge (1920) to drive inverter bridges with three-or-more levels. Signals from an ordinary induction motor controller or a two-level induction motor controller (2200) are used to drive the twelve-or-more switches of a three-or-more level inverter bridge (1920), as are used in medium-and-high voltage applications. The proper sequence and timing of switching for the three-or-more-level inverter bridge is based in-part upon either the output of the six pulse-width modulators, or the output of the flux and torque control device, or the voltage control device (2210), of the two-level controller (2200).

WO 2004/015851 A3

BEST AVAILABLE COPY